











代码 CODE	产品 product	规格 SPECIFICATION	附注 NOTES	厂家型号及编码 MODEL&PART CODE	交货时间 LEADTIME	是否认证CERTIFICATION	图片 IMAGE
1	Downlight 筒灯	<p>Materials: Plastic and Aluminum Shell Dimensions: Ø 115 * H60mm Color temperature: Three types of color temperature dimming Hole diameter: 90mm Power: 10W ± 10% Note: Tri color dimming, thyristor dimming, with Australian plug</p> <p>材料: 塑料和铝外壳 尺寸: Ø115*H60mm 色温: 三种色温调光方式 开孔孔径: 90mm 功率: 10W±10% 注: 三色调光, 可控硅调明暗, 带澳大利亚插头</p>	Downlight 筒灯	DL10W-3CCT	7 to 10 days 七到10天内	<p>YES</p> 	
2	Spotlight 射灯	<p>Material: Plastic and Aluminum Shell Size: Ø 103 * H88mm Color temperature: Three color temperature dimming methods Hole diameter: 90mm Power: 10W ± 10% Note: Tri color dimming, thyristor dimming, with Australian plug</p> <p>材料: 塑料和铝外壳 尺寸: Ø103*H88mm 色温: 三种色温调光方式 开孔孔径: 90mm 功率: 10W±10% 注: 三色调光, 可控硅调明暗, 带澳大利亚插头</p>	Spotlight 射灯	DLR03-C103	7 to 10 days 七到10天内	<p>YES</p> 	

3	Downlight 筒灯	<p>Material: Plastic and Aluminum Shell Size: Ø 108 * H70mm Color temperature: Three color temperature dimming methods Hole diameter: 95mm Power: 10W ± 10% Note: Tri color dimming, thyristor dimming, with Australian plug 材料材料: 塑料和铝外壳 尺寸: Ø108*H70mm 色温: 三种色温调光方式 开孔孔径: 95mm 功率: 10W±10% 注: 三色调光, 可控硅调明暗, 带澳大利亚插头</p>	Downlight 筒灯	DTF02-C108	7 to 10 days 七到10天内	<p>YES</p> 	
4	Downlight external power supply 筒灯 外置电源	<p>Material: Plastic and Aluminum Shell Size: Ø 108 * H46mm Color temperature: Three color temperature dimming methods Hole diameter: 95mm Power: 10W ± 10% Note: Tri color dimming, thyristor dimming, with Australian plug 材料: 塑料和铝外壳 尺寸: Ø108*H46mm 色温: 三种色温调光方式 开孔孔径: 95mm 功率: 10W±10% 注: 三色调光, 可控硅调明暗, 带澳大利亚插头</p>	Downlight external power supply 筒灯 外置电源	DF02-C108 concave surface	7 to 10 days 七到10天内	<p>YES</p> 	

5	Downlight external power supply 筒灯 外置电源	Materials: Plastic and Aluminum Shell Size: Ø 108 * H37mm Color temperature: Three color temperature dimming methods Hole diameter: 90mm Power: 10W ± 10% Note: Tri color dimming, thyristor dimming, with Australian plug 材料: 塑料和铝外壳 尺寸: Ø108*H37mm 色温: 三种色温调光方式 开孔孔径: 90mm 功率: 10W±10% 注: 三色调光, 可控硅调明暗, 带澳大利亚插头	Downlight external power supply 筒灯 外置电源	DF02-C108 plane	7 to 10 days 七到10天内	YES 	
6	Spotlight external power supply 射灯 外置电源	Materials: Plastic and Aluminum Shell Size: Ø 100 * H83mm Color temperature: Three color temperature dimming methods Hole diameter: 90mm Power: 13W ± 10% Note: Tri color dimming, thyristor dimming, with Australian plug 材料: 塑料和铝外壳 尺寸: Ø100*H83mm 色温: 三种色温调光方式 开孔孔径: 90mm 功率: 13W±10% 注: 三色调光, 可控硅调明暗, 带澳大利亚插头	Spotlight external power supply 射灯 外置电源	DSR03- C100(COB)	7 to 10 days 七到10天内	YES 